

BrightPath EMS 6.6/4.0

CommScope® Mid-Span Entry Tool

- Especially designed to mid-span access CommScope® BrightPath Self Support Figure 8 Outdoor Fiber Drop Cable
- Tool has two precise shaving channels, one to remove the outer MPDE jacket and one to access the 4mm buffer tube fibers
- Fixed control of blade cutting depth and angle protects fibers from damage
- Cable is easily inserted and removed by opening and closing spring loaded tool halves with a convenient and quick turning thumb screw
- Replacement Blade Part No. for A & B Channel: CB229
- Length: 3.75 in (95 mm)
- Weight: 6.8 oz (193 g)
- Part No.: 42555



405 Fiber Buffer Tube and Drop Cable Slitter

- For mid-span and end slitting of fiber buffer tubes and fiber drop cable
- Different models available matched to the size of buffer tube or drop cable to be prepared
- Dual blade design
- Self closing for safety
- Latch locks tool closed
- Comfortable soft plastic grips
- Made in the U.S.A.
- Replacement Blade Part No.: 80235 (2 required)
- Length: 6.5 in (165 mm)
- Weight: 9.0 oz (255 g)



Model	Part Number	Tube Size (mm OD)	Tube Size (inch OD)
405 – 1.8 mm	80800	1.6 – 1.8 mm	0.063" – 0.071"
405 – 2.0 mm	80805	1.8 – 2.0 mm	0.071" – 0.079"
405 – 2.2 mm	80801	2.0 – 2.2 mm	0.079" – 0.087"
405 – 2.5 mm	80802	2.3 – 2.5 mm	0.091" – 0.098"
405 – 3.0 mm	80803	2.7 – 3.0 mm	0.106" – 0.118"
405 – 3.3 mm	80804	3.0 – 3.3 mm	0.118" – 0.130"
*405 – Drop A	80256	4.4 x 8.2 mm	0.175" – 0.325"

* 405 – Drop A for OFS, CommScope and Corning Cable